

RECEIVED  
CENTRAL FAX CENTER  
AUG 09 2008

PATENT APPLN. NO. 10/762,530  
RESPONSE UNDER 37 C.F.R. §1.111

PATENT  
NON-FINAL

IN THE CLAIMS:

1. (previously presented)      A prefilled syringe comprising:  
a shoulder portion provided with a luer tip arranged to be  
connected to an injection needle at a tip thereof; a barrel closed  
by the shoulder portion and having an open proximal end; and a  
gasket inserted adjacent to the open proximal end of the barrel in  
a fluid-tight manner while being freely slidable, a medication  
being contained inside the barrel, wherein

the barrel has a multilayer structure in which an innermost  
layer and an outermost layer are both made of a polyolefin resin,  
and an intermediate layer is sandwiched by the innermost layer and  
the outermost layer and is composed of at least one layer made of  
a resin excelling in a barrier property,

and further wherein the intermediate layer is formed up to a  
vicinity of a surface of the tip of the luer tip, and is not formed  
in a direction of the proximal end of the barrel from a proximal  
end of an initial insertion position of the gasket inserted in the  
barrel.

2. (canceled)

3. (previously presented)      A prefilled syringe comprising:  
a shoulder portion provided with a luer tip arranged to be  
connected to an injection needle at a tip thereof; a barrel closed  
by the shoulder portion and having an open proximal end; and a  
gasket inserted adjacent to the open proximal end of the barrel in  
a fluid-tight manner while being freely slidable, a medication  
being contained inside the barrel, wherein

the barrel has a multilayer structure in which an innermost  
layer and an outermost layer are both made of a polyolefin resin,  
and an intermediate layer is sandwiched by the innermost layer and  
the outermost layer and is composed of at least one layer made of  
a resin excelling in a barrier property,

and further wherein:

an end of the intermediate layer in a cylindrical wall portion  
of the barrel is formed up to a rim of the shoulder portion;

the shoulder portion formed with the polyolefin resin has a  
thickness sufficient to exert a barrier property; and

the luer tip is sealed by a cap having a barrier property.

4 - 8. (canceled)